SERIES 500

BY **EXPI-DOOR**®



EXPI-DOOR®Systems Inc.

SERIES 500

STANDARD KEY FEATURES

The Series 500 is made of the best quality components, meeting commercial standards at a value oriented price. Compare the following:

Doors

18 gauge galvanized (A40), polyurethane core, R-Value 10.2, U-Value .10, ASTM C-518, square edge. Flush mounted top channel. Doors meet commercial Steel Door Institute (SDI) standards.

Frames

16 gauge galvanized (A40), 5 3/4" frame depth with 2" x 2" header and 4" x 1 3/4" subframe header. Frames meet commercial Steel Door Institute (SDI) standards.

Locks

Falcon Grade 2 W511-626-Dane. Thru bolted for strength. Free wheeling vandal resistant lever. Ten-year warranty.

16 gauge galvanized (A40 minimum) subjamb. Proprietary offset subjamb/jamb anchor system allows self-trimming; no jamb trim required. Flush subjamb also available, required for wind and fire-rated doors.

Paint Finish

All doors and frames are baked-on primer paint, meeting ANSI A250 Standards. Tested for salt spray, humidity, abrasion, and adhesion.

Hinges

Ball bearing silver powder coated hinges with security nonremovable pins.

Packaging

Doors are stacked on wood skid, connected through the subjambs, or with separation between for doors without subiambs. Doors are enclosed in OSB for protection during shipping.

Full 5 3/4" aluminum threshold,

dual finger TPE sweep, and urethane foam weatherseal for kerfless type application. All components meet commercial standards and ADA requirements.



The Series 500 is covered by a six-year warranty on the door leaf and frame, guaranteeing the product to be free of defects in materials and workmanship (certain hardware components have longer warranties).

OPTIONS



Wind & Fire Offering

Honeycomb core Warnock Hersey WH45, WH90, and WH180 minute label.



Grade 1 Lever Lock

Falcon Grade 1, T511-626-Dane, heavy-duty. Thru bolted for strength. Free wheeling vandal resistant lever. Ten-year warranty.



Mortise Lever Lock

Heavy duty grade 1 mortise lever lockset with escutcheon plate. 3/4" latch throw and 1" deadbolt throw. Ten-year warranty.



Exit Device

Heavy duty grade 1 rim exit device. Aluminum finish. Key-in-lever or escutcheon-with-lever trim. Ten-year warranty.



3146 Yeager Drive, Green Bay, WI 54311 Phone: 920-393-4028 Fax: 920-393-4452 www.expidoor.com



Auto Closer

Heavy duty grade 1 surface applied closer. Backcheck, sweep and latch speed adjustment valves. Ten-year warranty.



Latch Guard

Steel latch guard with chrome finish. Prevents tampering with the latch on lever locks.




9x30



24x30

SWING: SPECIFY USING CHART BELOW

INSIDE OF ROOM OR BUILDING



DI

(RH-Activ

Other terminology: LHR = A = RH = LHO

(left hand out)

PREASSEMBLED

PRODUCT

RHR = B = LH =RHO (right hand out)

OUTSIDE OF ROOM OR BUILDING